

Welded Pipe Nipples – Black & Galvanized Standard Schedule 40, XH Schedule 80



Specifications


Dimensions: ASTM A733 (See table below for standard sizes)

Threads: NPT per ASME B1.20.1

Material: ASTM A53 Welded Steel Pipe

Finish: Black, Hot Dip Galvanized, or Zinc Electroplated

Standard and Extra Heavy Right and Left Nipples available in 1/8" – 4" diameter and 4" or 6" lengths. See Special Design Pipe Nipples on page 5 for more information.



| Pipe Size | Pipe O.D. | Length Close | | | | | | | Pip | e Nipp | ole Lengt | hs | | | | | | |
|--------------|--------------|-----------------|-------|---|------|---|------|-----|------|--------|-----------|-----|-----|-----|---|-----|----|------|
| <u>in</u> | in | in | | | | | | | | | | | | | | | | |
| 1/8 | 0.405 | 3/4 | 11//2 | 2 | 21/2 | 3 | 31/2 | _ 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | _10 | 11 | 12 |
| 1/4 | 0.540 | 7/8 | 11//2 | 2 | 21/2 | 3 | 31/2 | 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 3/8 | 0.675 | 1 | 11//2 | 2 | 21/2 | 3 | 31/2 | 4 | 41/2 | 5 | 51/2 | 6 | _ 7 | 8 | 9 | 10 | 11 | _ 12 |
| 1/2 | 0.840 | 11/8 | 11/2 | 2 | 21/2 | 3 | 31/2 | 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 3/4 | 1.050 | 13/8 | 11/2 | 2 | 21/2 | 3 | 31/2 | 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 1 | 1.315 | 11/2 | | 2 | 21/2 | 3 | 31/2 | 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 11/4 | 1.660 | 15/8 | | 2 | 21/2 | 3 | 31/2 | 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 11/2 | 1.900 | 13/4 | | 2 | 21/2 | 3 | 31/2 | 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 2 | 2.375 | 2 | | | 21/2 | 3 | 31/2 | 4 | 41/2 | 5 | 51/2 | _ 6 | _ 7 | _ 8 | 9 | _10 | 11 | _ 12 |
| 21/2 | 2.875 | 21/2 | | | | 3 | 31/2 | 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 3 | 3.500 | 25/8 | | | | 3 | 31/2 | 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 31/2 | 4.000 | 23/4 | | | | | 31/2 | 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 4 | 4.500 | 27/8 | | | | | | 4 | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 5 | 5.563 | 3 | | | | | | | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| 6 | 6.625 | 31/8 | | | | | | | 41/2 | 5 | 51/2 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |

Note: Other lengths available upon request. 8" Pipe Size available as POA – contact your ASC Engineered Solutions™ Representative for details.

| APPROVAL STAMP |
|-------------------|
| Approved |
| Approved as noted |
| Not approved |
| Remarks: |
| |
| |
| |
| |





Specifications

Unless otherwise specified welded nipples ASTM A 53 are furnished on orders for steel nipples in standard and extra strong sizes $^{1}/_{8}$ " – 8" NPS (6 – 200 DN).

Welded steel nipples (A 53 Type F or Type E) are available in standard and extra strong sizes $\frac{1}{8}$ " – 8" NPS (6 – 200 DN), right hand threads, black or galvanized.

Seamless nipples manufactured for the U.S. and International markets are **not** phosphate coated. Seamless nipples manufactured for Canada **are** phosphate coated.

Seamless steel pressure tube nipples (ASTM A 106 Grade B) are available in standard and extra strong sizes ½" – 8" NPS (6 – 200 DN) with right hand threads, black only.

Right and left steel nipples are available in standard and extra heavy weight sizes $\frac{1}{8}$ " – 4" NPS (8 – 50 DN), in 4" (102mm) and 6" (152mm) lengths.

Nipples are available from stock in $\frac{1}{6}$ " – 8" NPS (6 – 200 DN) diameter, close to 12 NPS (300 DN) in length. Sizes 13" – 24" NPS (325 – 600 DN). (Prices on application.)

Steel pipe nipples meet ASTM A733.

1/8" Schedule 40 and 80 galvanized nipples are all electroplated.

Identification

Where possible, each seamless pipe nipple is identified with the following:

- A trade mark
- Seamless designation "SMLS"
- Pipe schedule 40, 80, 160, XXS
- Material designation
- Heat number for traceability

| Standards and Specifications | | | | | | | | | | | | |
|------------------------------------|------------|---------------------------|--------------|---------------|--|--|--|--|--|--|--|--|
| | Dimensions | Material | Thread | Federal/Other | | | | | | | | |
| | | Pipe Nipples | | | | | | | | | | |
| Steel Pipe - Welded | ASTM A733 | ASTM A53 Type F or Type E | ASME B1.20.1 | WWN 351 | | | | | | | | |
| Steel Pipe - Seamless (High Temp.) | ASTM A733 | ASTM A106 Gr. B | ASME B1.20.1 | WWN 351 | | | | | | | | |
| Brass | ASTM B687 | ASTM B43 | ASME B1.20.1 | WWN 351 | | | | | | | | |





Steel Pipe Nipples Welded – Ready Cut Pipe Standard – Schedule 40

"A" Assortments

Mixed Cartons (Black — Figure 339 & Galvanized — Figure 343)



| Nom. Pipe Size | Close | 11/2" | 2" | 2½" | 3" | 3½" | 4" | 4½" | 5" | 5½" | 6" | No. of Pieces | Approx. Wt. Lbs. |
|----------------------|-------|-------|----|-----|----|-----|----|-----|----|-----|----|------------------|------------------------|
| 1/2 | 4 | 3 | 3 | 3 | 2 | 2 | 2 | 1 | 2 | 1 | 2 | 25 | 5.00 |
| 1/2 | 20 | 10 | 15 | 10 | 10 | 5 | 10 | 5 | 5 | 5 | 5 | 100 | 18.00 |
| 3/4 | 4 | 3 | 3 | 3 | 2 | 2 | 2 | 1 | 2 | 1 | 2 | 25 | 7.00 |
| 3/4 | 20 | 10 | 15 | 10 | 10 | 5 | 10 | 5 | 5 | 5 | 5 | 100 | 24.00 |
| 1 | 15 | - | 15 | 10 | 12 | 5 | 5 | 4 | 3 | 3 | 3 | 75 | 24.00 |
| 1 | 5 | - | 5 | 3 | 2 | 2 | 2 | 1 | 2 | 1 | 2 | 25 | 10.00 |
| 11/4 | 5 | - | 5 | 3 | 2 | 2 | 2 | 1 | 2 | 1 | 2 | 25 | 12.00 |
| 11/2 | 5 | - | 5 | 3 | 2 | 2 | 2 | 1 | 2 | 1 | 2 | 25 | 15.00 |
| 2 | 6 | - | _ | 3 | 3 | 2 | 3 | 1 | 3 | 1 | 3 | 25 | 22.00 |

All items ship in bulk quantities.

"66" Packs or Assorted 6 Cartons

(Black — Figure 339 & Galvanized — Figure 343)



| Nom. Pipe Size | Close | 11/2" | 2" | 2 ½" | 3" | 3½" | 4" | 4½" | 5" | 5½" | 6" | No. of Pieces | Approx. Wt. Lbs. |
|-------------------|-------|-------|----|-------------|----|-----|----|-----|----|-----|----|------------------|---------------------|
| 1/8 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 6.00 |
| 1/4 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 9.00 |
| 3/8 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 12.00 |
| 1/2 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 14.00 |
| 3/4 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 19.00 |
| 1 | 6 | - | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 60 | 26.00 |
| 11/4 | 6 | _ | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 60 | 33.00 |
| 11/2 | 6 | - | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 60 | 41.00 |
| 2 | 6 | - | - | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 54 | 53.00 |

All items ship in bulk quantities.

Handy Pack Assortments

Mixed Cartons (Black - Figure 339 & Galvanized - Figure 343)



| Nom. Pipe Size | Close | 11/2" | 2" | 2 ½" | 3" | 31/2" | 4" | 41/2" | 5" | 5½" | 6" | No. of Pieces | Approx. Wt. Lbs. |
|-------------------|-------|-------|----|-------------|----|-------|----|-------|----|-----|----|------------------|---------------------|
| 1/8 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 6.00 |
| 1/4 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 9.00 |
| 3/8 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 12.00 |
| 1/2 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 14.00 |
| 3/4 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 19.00 |
| 1 | 6 | _ | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 60 | 26.00 |
| 111/4 | 3 | _ | - | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 27 | 19.00 |
| 111/2 | 3 | _ | - | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 27 | 23.00 |
| 2 | 3 | - | - | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 27 | 30.00 |

All items ship in bulk quantities.

Beck® Pipe Couplings



Steel Pipe Nipples

Welded - Ready Cut Pipe Standard - Schedule 40, XH Sch. 80

Single Run Packs

(Black — Figure 339 & Galvanized — Figure 343)



| Nom. Pipe Size | Close | 1½" | 2" | 2 ½" | 3" | 3½" | 4" | 4½" | 5" | 5½" | 6" | No. of Pieces | Approx. Wt. Lbs. |
|-------------------|-------|-----|----|-------------|----|-----|----|-----|----|-----|----|------------------|---------------------|
| 1/8 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 11 | 1.00 |
| 1/4 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 11 | 1.50 |
| 3/8 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 11 | 2.00 |
| 1/2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 11 | 2.50 |
| 3/4 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 11 | 3.50 |
| 1 | 1 | _ | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 10 | 5.00 |
| 11/4 | 1 | _ | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 10 | 7.00 |
| 11//2 | 1 | _ | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 10 | 8.00 |
| 2 | 1 | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 9 | 10.00 |
| 21/2 | 1 | - | - | _ | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 8 | 13.30 |
| 3 | 1 | - | - | _ | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 8 | 15.80 |

All items ship in bulk quantities.

Single Run Packs

(Black Only Extra Heavy — Figure 338)

| Nom. Pipe Size | Close | 11/2" | 2" | 2½" | 3" | 3½" | 4" | 4½" | 5" | 5½" | 6" | No. of Pieces | Approx. Wt. Lbs. |
|-------------------|-------|-------|----|-----|----|-----|----|-----|----|-----|----|------------------|---------------------|
| 1/2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 11 | 3.20 |
| 3/4 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 11 | 4.30 |
| 1 | 1 | _ | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 10 | 6.10 |
| 11/4 | 1 | _ | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 10 | 8.40 |
| 11//2 | 1 | _ | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 10 | 10.30 |
| 2 | 1 | _ | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 9 | 13.90 |

All items ship in bulk quantities.

Ready Cut Pipe

(Black Extra Long - Figure 339 & Galvanized - Figure 343)

| Nom. Pipe Size | 18" | 24" | 30" | 36" | 42" | 48" | 54" | 60" | 66" | 72" |
|-------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 1/8 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 |
| 1/4 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 |
| 3/8 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 |
| 1/2 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 |
| 3/4 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 |
| 1 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| 11/4 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| 11/2 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |

Travel Trays

(Black - Figure 339 & Galvanized - Figure 343)



| Nom. Pipe Size | Close | 1½" | 2" | 2½" | 3" | 3½" | 4" | 4½" | 5" | 5½" | 6" | No. of Pieces | Approx. Wt. Lbs. | _ |
|-------------------|-------|-----|----|-----|----|-----|----|-----|----|-----|----|------------------|---------------------|---|
| 1/2 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 15.00 | |
| 3/4 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 66 | 20.00 | |
| 1 | 5 | - | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 50 | 22.00 | |

All items ship in bulk quantities.



Special Design Pipe Nipples

Beck Pipe Nipples are available with a variety of options for customization. To order, begin by selecting the figure number, material, finish, and end treatments from the table below. Then, select the nominal pipe size and specify the length rounded to the nearest $^{1}/_{16}$ ". Contact your ASC Engineered SolutionsTM Representative for additional options.

| Fig. No. | Description | | Material | | Finish | E | nd #1 | E | nd #2 | NPS | Length |
|----------|--|----------|----------------------|---------------|---|----|-------|----------|-------|--|------------------------------|
| 33000 | Sch. 40 Seamless | Α | ASTM A106 GR B | Α | Plain with Zinc Phosphate Coating | Α | NPT | Α | NPT | 1/8 | |
| 320SD | Nipple Special Design | В | ASTM A333 | В | Plain with Sandblasted Surface | В | PLN | В | PLN | 1/ ₄ 3/ ₈ | |
| | | Α | ASTM A106 GR B | Α | Hot Dip Galvanized per ASTM A153 | С | PSQ | С | PSQ | ³ /8 ¹ / ₂ | |
| 330SD | Sch. 40 Seamless Nipple - Galvanized Special Design | В | ASTM A333 | В | Zinc Electroplated per ASTM B633 | D | PDB | D | PDB | 3/4 | |
| | Gatvariized Special Design | _ | - | C | Zinc Electroplated with Yellow Chromate | Е | ROE | E | ROE | 1 | Up to 24" |
| | XH/Sch. 80 Seamless | Α | ASTM A106 GR B | Α | Plain with Zinc Phosphate Coating | F | BEV | F | BEV | 11/ ₄ 11/ ₂ | Maximum Specify |
| 325SD | Nipple Special Design | В | ASTM A333 | В | Plain with Sandblasted Surface | G | NPL | | NPL | 2 | to the |
| | | Α | ASTM A106 GR B | Α | Hot Dip Galvanized per ASTM A153 | Н | NPM | | NPM | 21/2 | nearest 1/16" |
| 335SD | XH/Sch. 80 Seamless Nipple - | В | ASTM A333 | В | Zinc Electroplated per ASTM B633 | ı | ISO | | ISO | 3 4 | |
| | Galvanized Special Design | _ | _ | | Zinc Electroplated with Yellow Chromate | | GRV | | GRV | 5 | |
| | Sch. 160 Seamless | Α | ASTM A106 GR B | Α | Plain with Zinc Phosphate Coating | K | LHT | _ , K | | 6 | |
| 326SD | Nipple Special Design | В | ASTM A333 | В | Plain with Sandblasted Surface | | | | End C | odes | |
| | | Ā | ASTM A106 GR B | A | Hot Dip Galvanized per ASTM A153 | | | | | | [broad oor |
| 333SD | Sch. 160 Seamless Nipple - Galvanized | В | ASTM A333 | В | Zinc Electroplated per ASTM B633 | N | PT | | | | 「hread per RH) (TOE) |
| 55555 | Special Design | _ | - | C | Zinc Electroplated with Yellow Chromate | PI | LN | | Plair | Fnd/Ro | oller Cut |
| | XXH Seamless | Α | ASTM A106 GR B | A | Plain with Zinc Phosphate Coating | | SQ. | PI: | | | are or Saw Cut |
| 327SD | Nipple Special Design | В | ASTM A333 | В | Plain with Sandblasted Surface | | JQ | 1 (0 | | | |
| | | A | ASTM A106 GR B | A | Hot Dip Galvanized per ASTM A153 | PΙ | OB | | | nd Debu | Square Cut Irred |
| 329SD | XXH Seamless Nipple - | В | ASTM A333 | В | Zinc Electroplated per ASTM B633 | | | | | | <u> </u> |
| 32330 | Galvanized Special Design | _ | | C | Zinc Electroplated with Yellow Chromate | R | ЭE | | | ne Ena - nd with f | Square Cut Ream |
| | C. L. 40 W. L. L. L. L. | A | ASTM A53, Type F, CW | A | Plain with Zinc Phosphate Coating | RI | EV | S. | | | th 371/2° Bevel |
| 339SD | Sch. 40 Welded Nipple Special Design | В | | B | Plain with Sandblasted Surface | | | | | | |
| | | A | ASTM A53, Type E, EW | <u>В</u> | | Ν | PL | NPSL | | :Thread ocknut) | per ASME B1.20.1 (Toe) |
| 24200 | Sch. 40 Welded Nipple - | | ASTM A53, Type F, CW | | Hot Dip Galvanized per ASTM A153 | | | | | | |
| 343SD | Galvanized Special Design | B | ASTM A53, Type E, EW | В | Zinc Electroplated per ASTM B633 | NF | PM | NF | | | ead per ASME nical) (Toe) |
| | | | - ACTM AED T F CM | <u>C</u> | Zinc Electroplated with Yellow Chromate | | | ıco | | <u> </u> | |
| 338SD | XH/Sch. 80 Welded NippleSpecial Design | <u>A</u> | ASTM A53, Type F, CW | <u>A</u> | Plain with Zinc Phosphate Coating | | 0 | | | | eads per ISO 7/1 |
| | | В | ASTM A53, Type E, EW | B | Plain with Sandblasted Surface | U | | | | | ASC Specification |
| 24260 | XH/Sch. 80 Welded | <u>A</u> | ASTM A53, Type F, CW | <u>A</u> | Hot Dip Galvanized per ASTM A153 | Lŀ | НT | NPT-I | | : Hande 1E B.1.20 | d NPT Thread per 11(TOF) |
| 342SD | Nipple - Galvanized Special Design | В | ASTM A53, Type E, EW | | Zinc Electroplated per ASTM B633 | | | | ۸۵۱۷ | IL D.1.20 | (10L) |
| | | _ | | C | Zinc Electroplated with Yellow Chromate | | | | _ | | |
| | Tank Nipple - | | | Α_ | Plain with Zinc Phosphate Coating | | | , | | | |
| 341SD | Sch. 40 Welded | Α | ASTM A53, Type E, EW | <u>В</u> С | Plain with Sandblasted Surface | | | (| | | |
| | Special Design | | | | Zinc Electroplated per ASTM B633 | | | | | | |
| | | _ | | D | Zinc Electroplated with Yellow Chromate | | | | | | |
| | **Dtt Nicolo | Α | ASTM A53, Type F, CW | Α | Plain with Zinc Phosphate Coating | | | | ^ | | |
| 344SD | **Butt Nipple - Sch. 40 Welded | | . 31 | В | Plain with Sandblasted Surface | | | | | | |
| | Special Design | В | ASTM A53, Type E, EW | C | Zinc Electroplated per ASTM B633 | | | | | | |
| | | | | D | Zinc Electroplated with Yellow Chromate | | | | | | |
| | Agrico Agrico | | | Α | Plain with Zinc Phosphate Coating | | | | | | |
| 345SD | Mining Nipple - Sch. 40 Welded | Α | ASTM A53, Type E, EW | В | Plain with Sandblasted Surface | | | | | M (| |
| | Special Design | • | , -, pc -, (| С | Zinc Electroplated per ASTM B633 | | | | | \ \ | _ |
| | | | | D | Zinc Electroplated with Yellow Chromate | | | | | | |
| 362SD | Special Design Seamless Nipple Brass & Chromium | Α | ASTM B43 Brass | Α | Plain | | | | | /. | |
| 30230 | Plated Brass | _ | ננפוט כדט ויווכא | В | Chrome Plated | | | | | |) |
| 363SD | Special Design Grooved Adapter | Α | ASTM B43 Brass | Α | Plain | | | | | 11 | |
| JUJ3U | Nipple - Aluminum & Brass | \sim | KSPIU CHU INI CH | В | Chrome Plated | | | | | ~ | ~ |

^{**} NPS and lengths available POA, upon request. Contact your ASC Engineered Solutions™ Representative for details.



Weight 0.13

0.20

0.28

0.40

0.53

0.76

1.04

1.28

1.56

Length

6

6

6

6

6

6

6


6

6

Special Design Pipe Nipples

Tank Nipples

Fig. 341SD - Black & Galvanized



| | _ |
|---|---|
| Tank Nipples are recommended for use as tank | |
| legs, not intended for pressure service. | |
| Tank Nipples have standard NPT threads on one | _ |
| end and straight NPSM threads running for 4" on | |
| the other end. Tank Nipples are fabricated from | |
| ASTM A53 Schedule 40 welded pipe. | _ |
| ron rossociación rometaca pipe. | |

Description

All Tank Nipples ship in quantities of 25. Not intended for pressure service.

Butt Nipples

Fig. 344SD - Black & Galvanized



Butt Nipples are intended for joining couplings or female threaded components end to end without exposing male threads. Butt Nipples have standard NPT male threads on both ends. Threads may have fewer imperfect threads due to reduced nipple length. Butt Nipples are fabricated from ASTM A53 Schedule 40 welded pipe.

Description

| Size | Length | Weight | Quantity |
|------|--------|--------|----------|
| 2 | 11/4 | 0.28 | 25 |
| 21/2 | 2 | 0.87 | 10 |
| 3 | 2 | 1.28 | 10 |
| 4 | 21/4 | 1.11 | 5 |

Right & Left Nipples

Black — Figure 339SD & Galvanized — Figure 343SD

Size

1/8

1/4

3/8

1/2

3/4

1

11/4

11/2

2

| Nom. Pipe Size | Length | Weight | Quantity |
|-------------------|----------|--------|----------|
| 1/8 | 4" or 6" | 0.09 | - |
| 1/4 | 4" or 6" | 0.13 | - |
| 3/8 | 4" or 6" | 0.18 | 25 |
| 1/2 | 4" or 6" | 0.25 | 25 |
| 3/4 | 4" or 6" | 0.35 | 25 |
| 1 | 4" or 6" | 0.51 | 25 |
| 11//4 | 4" or 6" | 0.68 | 25 |
| 11//2 | 4" or 6" | 0.80 | 25 |
| 2 | 4" or 6" | 1.09 | 25 |
| 21/2 | 4" or 6" | 1.50 | _ |
| 3 | 4" or 6" | 2.00 | - |
| 31/2 | 4" or 6" | 2.80 | _ |
| 4 | 4" or 6" | 3.24 | _ |

General Assembly of Threaded Fittings

Inspect both male and female components prior to assembly.

- · Threads should be free from mechanical damage, dirt, chips and excess cutting oil.
- Clean or replace components as necessary.

2. Application of thread sealant

- Use a thread sealant that is fast drying, sets-up to a semi hard condition and is vibration resistant.
 Alternately, an anaerobic sealant may be utilized.
- Thoroughly mix the thread sealant prior to application.
- Apply a thick even coat to the male threads only. Best application is achieved with a brush stiff enough to force sealant down to the root of the threads.

3. Joint Makeup

- For sizes up to and including 2" pipe, wrench tight makeup is considered three full turns past handtight. Handtight engagement for ½" through 2" thread varies from 4½ turns to 5 turns.
- For 2½" through 4" sizes, wrench tight makeup is considered two full turns past handtight. Handtight engagement for 2½" through 4" thread varies from 5½ turns to 6¾ turns.

