

Cap
Fig. 7074*



 - Available galvanized

Material Specifications

Cast Fittings

Ductile Iron conforming to ASTM A536

Coatings

Rust inhibiting paint

Color: ORANGE (Standard)

Hot Dipped Zinc Galvanized conforming to ASTM A153 (Optional)

Other available options
(Example: RAL3000 or RAL9000 Series)


For Listings/Approval Details and Limitations, visit our website at www.asc-es.com or contact an ASC Engineered Solutions™ Sales Representative.

*When ordering, refer to product as FP7074.



PROJECT INFORMATION	APPROVAL STAMP
Project:	Approved
Address:	Approved as noted
Contractor:	Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	

Cap Fig. 7074*



Nominal Size	O.D.	End to End	Approx. Wt. Ea.	Nominal Size	O.D.	End to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./kg	In./DN(mm)	In./mm	In./mm	Lbs./kg
1 25	1.315 33.4	1¼ 32	0.3 0.1	5½ O.D. 139.7	5.500 139.7	1⅞ 29	4.0 1.8
1¼ 32	1.660 42.2	1¼ 32	0.4 0.2	5 125	5.563 141.3	1⅞ 29	4.0 1.8
1½ 40	1.900 48.3	1¼ 32	0.5 0.2	6½ O.D. 165.1	6.500 165.1	1⅞ 29	6.0 2.7
2 50	2.375 60.3	1 25	0.5 0.2	6 150	6.625 168.3	1⅝ 33	6.0 2.7
2½ 65	2.875 73.0	1 25	0.7 0.3	8 200	8.625 219.1	1½ 38	12.5 5.7
3 O.D. 76.1	2.996 76.1	1 25	0.8 0.4	10 250	10.750 273.1	1½ 38	21.9 9.9
3 80	3.500 88.9	1 25	1.1 0.5	12 300	12.750 323.9	1½ 38	33.8 15.3
4 100	4.500 114.3	1⅞ 29	2.8 1.3				

Note:

Additional sizes available, see Gruvlok Catalog or contact an ASC Engineered Solutions™ Representative.



asc-es.com

Building connections that last™