



Constant Support

Check List for Requesting a Quote or Ordering

Page ___ of ___

Finish: Standard Primer: _____ Galvanized: _____ Special Coating: _____

Quantity: _____

Figure No.: Options are: 80-V, 81-H
or: C-80-V, C-81-H

Size: Options are: #1 through #110 (Size #1 through #9 available in 81-H only)

Type: Options are: A through G* (Type F Upthrust available in 81-H only, Type G available in 80-V only)

Actual Travel (AT): _____ (inches)

Total Travel (TT):** _____ (inches)

Direction of Travel: _____ + (up) or - (down)

Load: _____ (lbs)

"J" Dimension: _____ (inches) (Not required for Type F)

Mark Number: _____ (If required)

Lifting Lugs: Yes: _____ No: _____

Available on sizes 10 and larger.

Notes:

* *Type G Constants must also include the C-to-C dimension & the load per spring.*

** *Total Travel = Actual travel + 1" or 20%, whichever is greater rounded up to the next one half inch increment.*

For technical information regarding Constant Supports contact:
Phone Number: (401) 886-3020 Email: eps_contact@anvilintl.com

ASC Engineered Solutions

Power & Process Division

160 Frenchtown Road, North Kingstown, RI 02852

T 401-886-3000 F 401-886-3010

www.asc-es.com