

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)  
 Issue date: 9/22/2020 Revision date: 7/6/2021 Version: 2.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : Paint-Riter™ Valve Action Paint Marker White, Yellow, Red, Blue, Green, Orange, Aluminum, Pink, Light Blue, Light Green, Brown, Gold

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Marking.  
 Restrictions on use : Any use not specified

#### 1.3. Supplier

LA-CO Industries  
 1201 Pratt Blvd.  
 Elk Grove Village, IL, 60007-5746  
 US  
 T 847-956-7600 - F 847-956-9885  
[customer\\_service@laco.com](mailto:customer_service@laco.com)



#### 1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887;  
 全国应急中心 0532 8388 9090

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Flammable liquids, Category 2	H225	Highly flammable liquid and vapour.
Skin sensitisation, category 1B	H317	May cause an allergic skin reaction.
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.

Full text of H-statements: see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) : Danger

Hazard statements (GHS\_US) : H225 - Highly flammable liquid and vapour.  
 H317 - May cause an allergic skin reaction.  
 H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 - Keep container tightly closed.  
 P240 - Ground/bond container and receiving equipment  
 P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P272 - Contaminated work clothing must not be allowed out of the workplace.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.

## Safety Data Sheet

P302+P352 - If on skin: Wash with plenty of water.  
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 P312 - Call a poison center/doctor if you feel unwell  
 P321 - Specific treatment (see supplemental first aid instruction on this label).  
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
 P362+P364 - Take off contaminated clothing and wash it before reuse.  
 P370+P378 - In case of fire: Use media other than water to extinguish.  
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 - Store in a well-ventilated place. Keep cool.  
 P405 - Store locked up.  
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No data available

### 2.4. Unknown acute toxicity (GHS\_US)

0.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

0.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

0.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
1-Methoxy-2-propanol	CAS-No.: 107-98-2	20 - 80	Flam. Liq. 3, H226 STOT SE 3, H336
Titanium dioxide	CAS-No.: 13463-67-7	0 - 25	Carc. 2, H351
Ethanol	CAS-No.: 64-17-5	10 - 20	Flam. Liq. 2, H225
Aluminium	CAS-No.: 7429-90-5	0 - 10	Flam. Sol. 1, H228 Water-react. 2, H261
Isopropanol	CAS-No.: 67-63-0	1 - < 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Rosin, fumarated, polymer with ethylene glycol and pentaerythritol	CAS-No.: 68152-57-8	1 - < 5	Eye Irrit. 2A, H319 Skin Sens. 1B, H317 Aquatic Chronic 4, H413
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)	CAS-No.: 2786-76-7	0 - 5	Skin Sens. 1, H317
[N,N,N',N'',N'''-hexaethyl-29H,31H-phthalocyaninetrimethylamino(2-)-N29,N30,N31,N32]copper	CAS-No.: 28654-73-1	0 - 1	Skin Sens. 1B, H317

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel

**Safety Data Sheet**

First-aid measures after inhalation	: unwell. : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin thoroughly with mild soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water.
First-aid measures after ingestion	: Do NOT induce vomiting. Get medical advice/attention.

**4.2. Most important symptoms and effects (acute and delayed)**

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

**4.3. Immediate medical attention and special treatment, if necessary**

Treat symptomatically.

**SECTION 5: Fire-fighting measures****5.1. Suitable (and unsuitable) extinguishing media**

Suitable extinguishing media	: Carbon dioxide. Dry chemical. Inert gas. Foam. Water spray. Water fog.
Unsuitable extinguishing media	: Do not use a heavy water stream.

**5.2. Specific hazards arising from the chemical**

Fire hazard	: Highly flammable liquid and vapour. Burning produces irritating, toxic and noxious fumes. Flammable vapours may accumulate in the container. Heavier than air, vapours may travel long distances along ground, ignite and flash back to source.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO <sub>2</sub> ). Hydrocarbon.

**5.3. Special protective equipment and precautions for fire-fighters**

Firefighting instructions	: Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses. Eliminate all ignition sources if safe to do so.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.
------------------	--

**6.1.1. For non-emergency personnel**

Protective equipment	: Refer to section 8.2.
Emergency procedures	: Evacuate unnecessary personnel.

**6.1.2. For emergency responders**

Protective equipment	: Refer to section 8.2.
Emergency procedures	: Stop leak if safe to do so. Ventilate area.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

For containment	: Eliminate all ignition sources. Stop the flow of material, if this is without risk.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Take up in non-combustible absorbent material and shove into container for disposal.

**6.4. Reference to other sections**

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

**SECTION 7: Handling and storage**

## Safety Data Sheet

### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	: No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid all eye and skin contact and do not breathe vapour and mist. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container tightly closed. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible products	: Strong oxidizers.
Incompatible materials	: Heat sources.
Heat and ignition sources	: Keep away from heat, sparks and flame.
Prohibitions on mixed storage	: Keep away from incompatible materials.
Storage area	: Store in dry, cool, well-ventilated area.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Paint-Riter™ Valve Action Paint Marker White, Yellow, Red, Blue, Green, Orange, Aluminum, Pink, Light Blue, Light Green, Brown, Gold

No data available

#### 1-Methoxy-2-propanol (107-98-2)

##### USA - ACGIH - Occupational Exposure Limits

Local name	1-Methoxy-2-propanol
ACGIH TWA (mg/m <sup>3</sup> )	369 mg/m <sup>3</sup>
ACGIH OEL TWA [ppm]	50 ppm
ACGIH STEL (mg/m <sup>3</sup> )	553 mg/m <sup>3</sup>
ACGIH OEL STEL [ppm]	100 ppm
Remark (ACGIH)	Eye irr; CNS impair; A4 (Not classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories)

##### USA - NIOSH - Occupational Exposure Limits

NIOSH REL TWA	360 mg/m <sup>3</sup>
NIOSH REL TWA [ppm]	100 ppm
NIOSH REL STEL	540 mg/m <sup>3</sup>
NIOSH REL STEL [ppm]	150 ppm

#### Rosin, fumarated, polymer with ethylene glycol and pentaerythritol (68152-57-8)

No data available

#### Titanium dioxide (13463-67-7)

##### USA - ACGIH - Occupational Exposure Limits

Local name	Titanium dioxide
ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)

<b>Titanium dioxide (13463-67-7)</b>	
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Titanium dioxide (Total dust)
OSHA PEL TWA [1]	15 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>Ethanol (64-17-5)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Ethanol
ACGIH TWA (mg/m <sup>3</sup> )	1884 mg/m <sup>3</sup>
ACGIH OEL TWA [ppm]	1000 ppm
ACGIH OEL STEL [ppm]	1000 ppm
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Ethyl alcohol (Ethanol)
OSHA PEL TWA [1]	1900 mg/m <sup>3</sup>
OSHA PEL TWA [2]	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	1900 mg/m <sup>3</sup>
NIOSH REL TWA [ppm]	1000 ppm
<b>Isopropanol (67-63-0)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	2-Propanol
ACGIH TWA (mg/m <sup>3</sup> )	490 mg/m <sup>3</sup>
ACGIH OEL TWA [ppm]	200 ppm
ACGIH STEL (mg/m <sup>3</sup> )	960 mg/m <sup>3</sup>
ACGIH OEL STEL [ppm]	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2021
<b>USA - ACGIH - Biological Exposure Indices</b>	
Local name	2-PROPANOL
BEI	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns

<b>Isopropanol (67-63-0)</b>	
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Isopropyl alcohol
OSHA PEL TWA [1]	980 mg/m <sup>3</sup>
OSHA PEL TWA [2]	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	980 mg/m <sup>3</sup>
NIOSH REL TWA [ppm]	400 ppm
NIOSH REL STEL	1225 mg/m <sup>3</sup>
NIOSH REL STEL [ppm]	500 ppm
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
No data available	
<b>[N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylamino(2-)-N29,N30,N31,N32]copper (28654-73-1)</b>	
No data available	
<b>Aluminium (7429-90-5)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Aluminum metal and insoluble compounds
ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pneumoconiosis; LRT irr; neurotoxicity. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Aluminum Metal (as Al)
OSHA PEL TWA [1]	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	10 mg/m <sup>3</sup>
NIOSH REL C	5 mg/m <sup>3</sup>
Remark (NIOSH)	(total dust)

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust ventilation of closed transfer systems to minimize exposures. Avoid creating mist or spray. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures/Personal protective equipment

**Personal protective equipment:**

Avoid all unnecessary exposure.

**Hand protection:**

In case of repeated or prolonged contact wear gloves. Butyl rubber gloves. short term. nitrile rubber gloves

**Eye protection:**

Chemical goggles or safety glasses

**Respiratory protection:**

None under normal use

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Variable
Odour	: Solvent
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 78.3 °C
Flash point	: 12.2 °C
Relative evaporation rate (butylacetate=1)	: < 1
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: 11.8
Relative vapour density at 20 °C	: No data available
Relative density	: 1 – 1.33
Solubility	: insoluble in water.
Log Pow	: 0.7
Auto-ignition temperature	: 287 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

**9.2. Other information**

VOC content : 50 – 60 %

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No dangerous reactions known.

**10.2. Chemical stability**

Flammable liquid and vapour.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Open flame. Overheating. Direct sunlight. Heat. Sparks.

**10.5. Incompatible materials**

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

May release flammable gases. Burning produces irritating, toxic and noxious fumes. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>Paint-Riter™ Valve Action Paint Marker White, Yellow, Red, Blue, Green, Orange, Aluminum, Pink, Light Blue, Light Green, Brown, Gold</b>	
Unknown acute toxicity (GHS_US)	0.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 0.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 0.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
<b>1-Methoxy-2-propanol (107-98-2)</b>	
LD50 Oral rat	4016 mg/kg bodyweight
LD50 Dermal rat	> 2000 mg/kg bodyweight
LC50 Inhalation rat [ppm]	> 7000 ppm 6 hr
<b>Titanium dioxide (13463-67-7)</b>	
LD50 Oral rat	> 5000 mg/kg
LC50 Inhalation rat	> 6.82 mg/l/4h
<b>Ethanol (64-17-5)</b>	
LD50 Oral rat	10470 mg/kg
LD50 Dermal rabbit	> 20000 mg/kg
LC50 Inhalation rat	133.8 mg/l/4h
ATE (oral)	10470 mg/kg bodyweight
ATE (vapours)	133.8 mg/l/4h
ATE (dust,mist)	133.8 mg/l/4h
<b>Isopropanol (67-63-0)</b>	
LD50 Oral rat	5840 mg/kg
LD50 Dermal rabbit	16.4 ml/kg
LC50 Inhalation rat [ppm]	> 10000 ppm/4h
ATE (oral)	5840 mg/kg bodyweight
ATE (dermal)	16400 mg/kg bodyweight
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
LD50 Oral rat	> 15000 mg/kg
LC50 Inhalation rat	> 1580 mg/m <sup>3</sup> 4 h
<b>[N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)</b>	
LD50 Oral rat	> 10000 mg/kg
LD50 Dermal rat	> 2500 mg/kg



## Safety Data Sheet

<b>Aluminium (7429-90-5)</b>	
LD50 Oral rat	> 15900 mg/kg
LC50 Inhalation rat	> 2.3 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified. (The chemicals used are not available in the physical form known to cause cancer.)

<b>Titanium dioxide (13463-67-7)</b>	
NOAEL (chronic, oral, animal/male, 2 years)	5 mg/kg bodyweight rat
Additional data	Carcinogen, cat 1A or 1B Inhalation of dust
IARC group	2B - Possibly carcinogenic to humans

<b>Ethanol (64-17-5)</b>	
IARC group	1 - Carcinogenic to humans, Alcoholic beverages

<b>Isopropanol (67-63-0)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

<b>1-Methoxy-2-propanol (107-98-2)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>Isopropanol (67-63-0)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Likely routes of exposure	: Inhalation. Skin and eye contact.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>1-Methoxy-2-propanol (107-98-2)</b>	
LC50 fish 1	20800 mg/l
EC50 crustacea	23300 mg/l
ErC50 algae	> 1000 mg/l

<b>Ethanol (64-17-5)</b>	
LC50 fish 1	14200 mg/l
EC50 crustacea	5012 mg/l

<b>Isopropanol (67-63-0)</b>	
------------------------------	--

<b>Isopropanol (67-63-0)</b>	
LC50 fish 1	10000 mg/l
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
LC50 fish 1	> 500 mg/l 96 h
EC50 crustacea	> 110 mg/l 48 h
<b>[N,N,N',N'',N'''-hexaethyl-29H,31H-phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)</b>	
LC50 fish 1	> 146 mg/l 96 h
EC50 crustacea	> 100 mg/l 48 h
<b>Aluminium (7429-90-5)</b>	
LC50 fish 1	218.64 mg/l ASTM 2000; test material: aluminium chloride hexahydrate; Pimephales promelas
EC50 crustacea	1.4 mg/l OECD Guideline 202; test material: Aluminium hydroxide
LOEC (acute)	≈ 72.89 mg/l
NOEC (acute)	≈ 37.2 mg/l

### 12.2. Persistence and degradability

<b>Paint-Riter™ Valve Action Paint Marker White, Yellow, Red, Blue, Green, Orange, Aluminum, Pink, Light Blue, Light Green, Brown, Gold</b>	
Persistence and degradability	Not established.
<b>1-Methoxy-2-propanol (107-98-2)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	96 % 28 d
<b>Ethanol (64-17-5)</b>	
Biodegradation	> 96 % 28 d
<b>Isopropanol (67-63-0)</b>	
Persistence and degradability	Readily biodegradable.
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % 28 d

### 12.3. Bioaccumulative potential

<b>Paint-Riter™ Valve Action Paint Marker White, Yellow, Red, Blue, Green, Orange, Aluminum, Pink, Light Blue, Light Green, Brown, Gold</b>	
Log Pow	0.7
Bioaccumulative potential	Not established.
<b>1-Methoxy-2-propanol (107-98-2)</b>	
Bioaccumulative potential	Not expected to bioaccumulate.
<b>Ethanol (64-17-5)</b>	
Bioaccumulative potential	Not expected to bioaccumulate.
<b>Isopropanol (67-63-0)</b>	

Isopropanol (67-63-0)	
Bioaccumulative potential	Not expected to bioaccumulate.
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
BCF fish 1	53 l/kg
Log Pow	1.28

### 12.4. Mobility in soil

Paint-Riter™ Valve Action Paint Marker White, Yellow, Red, Blue, Green, Orange, Aluminum, Pink, Light Blue, Light Green, Brown, Gold	
Ecology - soil	No data available.

### 12.5. Other adverse effects

Other information : No data available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
 Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
 Additional information : Handle empty containers with care because residual vapours are flammable.

## SECTION 14: Transport information

### 14.1. UN number

DOT NA No : UN1263  
 UN-No. (TDG) : UN 1263  
 UN-No. (IMDG) : 1263  
 UN-No. (IATA) : 1263

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base)  
 Proper Shipping Name (TDG) : PAINT  
 Proper Shipping Name (IMDG) : PAINT  
 Proper Shipping Name (IATA) : PAINT

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 3  
 Hazard labels (DOT) : 3



#### TDG

Transport hazard class(es) (TDG) : 3

#### IMDG

Transport hazard class(es) (IMDG) : 3  
 Danger labels (IMDG) : 3


**IATA**

 Transport hazard class(es) (IATA) : 3  
 Danger labels (IATA) : 3

**14.4. Packing group**

 Packing group (DOT) : II  
 Packing group (TDG) : II  
 Packing group (IMDG) : II  
 Packing group (IATA) : II

**14.5. Environmental hazards**

Other information : No supplementary information available.

**SECTION 15: Regulatory information**
**15.1. US Federal regulations**

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Isopropanol	CAS-No. 67-63-0	1 - < 5%
Aluminium	CAS-No. 7429-90-5	0 - 10%

**Isopropanol (67-63-0)**

SARA Section 311/312 Hazard Classes	Fire hazard
-------------------------------------	-------------

**15.2. International regulations**
**Paint-Riter™ Valve Action Paint Marker White, Yellow, Red, Blue, Green, Orange, Aluminum, Pink, Light Blue, Light Green, Brown, Gold**

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

**Rosin, fumarated, polymer with ethylene glycol and pentaerythritol (68152-57-8)**

 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on Taiwan National Chemical Inventory  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Not listed on Phillipines Inventory of Chemicals and Chemical Substances (PICCS)  
 Unlisted introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
 Listed on KECL/KECI (Korean Existing Chemicals Inventory)

**Titanium dioxide (13463-67-7)**

 Listed on IARC (International Agency for Research on Cancer)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)

### Titanium dioxide (13463-67-7)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Listed on Taiwan National Chemical Inventory  
 Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
 Listed on the TCSI (Taiwan Chemical Substance Inventory)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on the Japanese ISHL (Industrial Safety and Health Law)  
 Listed on KECL/KECI (Korean Existing Chemicals Inventory)

### Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

### 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
 Listed on Taiwan National Chemical Inventory  
 Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on KECL/KECI (Korean Existing Chemicals Inventory)

### [N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrithylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on Taiwan National Chemical Inventory  
 Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on KECL/KECI (Korean Existing Chemicals Inventory)

### Aluminium (7429-90-5)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on the Chinese Catalog of Hazardous Chemicals.  
 Listed on the TCSI (Taiwan Chemical Substance Inventory)  
 Listed on KECL/KECI (Korean Existing Chemicals Inventory)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

### 15.3. US State regulations

#### Paint-Riter™ Valve Action Paint Marker White, Yellow, Red, Blue, Green, Orange, Aluminum, Pink, Light Blue, Light Green, Brown, Gold

State or local regulations	The titanium dioxide in this product is bound and is not respirable. California Prop. 65 warnings are not required.
----------------------------	--

Component	State or local regulations
1-Methoxy-2-propanol(107-98-2)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Titanium dioxide(13463-67-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

## Safety Data Sheet

Component	State or local regulations
Ethanol(64-17-5)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Isopropanol(67-63-0)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Aluminium(7429-90-5)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information


Revision date	: 07/06/2021
Data sources	: ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <a href="http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database">http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database</a> . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <a href="http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html">http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html</a> .
Other information	: None.

Full text of H-statements	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H261	In contact with water releases flammable gases.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H413	May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms	
	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration

Abbreviations and acronyms	
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weighted Average
	TSCA: Toxic Substances Control Act

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:
Composition/information on ingredients.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.