

## WARDFlex® Tubing & Components Flush Mount Gas Valve Kit



### Components

- Valve Body
- Retainer Ring
- Adapter Nut
- Gasket
- Box
- Cover

### Listings

- CSA: File # 112940\_0\_000
- IAPMO: File # 3353
- ICC: Report # ESR-1879

### Technical Data

#### General

**Certified Operating Pressure**  
25 psi

#### Materials

**Body, Retainer Ring & Adapter Nut**  
Brass

**Valve Handle**  
Steel (Painted Yellow)

**Gasket**  
Composite Fiber

**Box and Cover**  
ABS, White

The 3/8" through 1 1/4" WARDFlex® tubing is terminated using the patented, STEPSAVER double seal fitting. The 1 1/2" and 2" tubing utilize the WARDFlex® traditional gasketed fitting design. Only fittings designed and listed for use with the WARDFlex® and WARDFlex® MAX CSST Piping Systems shall be used when connecting to the flexible piping.

### Features

- Provides flush mount termination for appliance connections
- Easy Installation

### Dimensions

Price Sheet Item #	CSST Size	NPT Size	Nut Hex	Box Dimensions	Approximate Weight (lbs)
701	1/2"	1/2"	1 3/16"	6.80"H x 6.80"W x 3.10"D	1.25
702	3/4"	1/2"	1 1/2"	6.80"H x 6.80"W x 3.10"D	1.40
703	3/4"	3/4"	1 1/2"	6.80"H x 6.80"W x 3.10"D	1.58



PROJECT INFORMATION	APPROVAL STAMP
Project:	Approved
Address:	Approved as noted
Contractor:	Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	