

## WARDFlex® Tubing & Components Right Angle Valve



The 3/8" through 1 1/4" WARDFlex® tubing is terminated using the patented, STEPSAVER double seal fitting. The 1 1/2" and 2" tubing utilize the WARDFlex® traditional gasketed fitting design. Only fittings designed and listed for use with the WARDFlex® and WARDFlex® MAX CSST Piping Systems shall be used when connecting to the flexible piping.

### Features

- Female NPT thread
- Gas shut off valve
- One corrugation crush seal
- Reusable
- Patented STEPSAVER fittings
  - Primary metal to metal seal
  - Secondary gasket seal

### Dimensions

Price Sheet Item #	CSST Size	NPT Size	Nut Hex	Maximum Tightening Torque (ft-lbs)	Approximate Weight (lbs)
410	1/2"	1/2"	1 1/16"	50	0.71
411	3/4"	1/2"	1 1/2"	120	0.86

### Components

- Valve Body
- Retainer Ring
- Nut
- Gasket

### Listings

- CSA: File # 112940\_0\_000
- IAPMO: File # 3353
- ICC: Report # ESR-1879

### Technical Data

#### General

**Certified Operating Pressure**  
25 psi

#### Materials

**Body, Retainer Ring & Nut**  
Brass

**Valve Handle**  
Steel (Painted Yellow)

**Gasket**  
Composite Fiber



PROJECT INFORMATION	APPROVAL STAMP
Project:	Approved
Address:	Approved as noted
Contractor:	Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	