

WARDFlex® Tubing & Components Valve



The 3/8" through 1 1/4" WARDFlex® tubing is terminated using the patented, STEPSAVER double seal fitting. The 1 1/2" and 2" tubing utilize the WARDFlex® traditional gasketed fitting design. Only fittings designed and listed for use with the WARDFlex® and WARDFlex® MAX CSST Piping Systems shall be used when connecting to the flexible piping.

Features

- Male NPT thread
- Gas shut off valve
- One corrugation crush seal
- Reusable
- Patented STEPSAVER fittings
 - Primary metal to metal seal
 - Secondary gasket seal

Dimensions

Price Sheet Item #	CSST Size	NPT Size	Nut Hex	Maximum Tightening Torque (ft-lbs)	Approximate Weight (lbs)
370	3/8"	1/2"	1 1/16"	50	0.64
371	1/2"	1/2"	1 3/16"	50	0.55
372	3/4"	3/4"	1 1/2"	120	1.02
373	1"	3/4"	1 3/4"	160	1.13

Components

- Valve Body
- Retainer Ring
- Nut
- Gasket

Listings

- CSA: File # 112940_L0_000
- IAPMO: File # 3353
- ICC: Report # ESR-1879

Technical Data

General

Certified Operating Pressure
25 psi

Materials

Body, Retainer Ring & Nut
Brass

Valve Handle
Steel (Painted Yellow)

Gasket
Composite Fiber



PROJECT INFORMATION	APPROVAL STAMP
Project:	Approved
Address:	Approved as noted
Contractor:	Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	